

EPS[®] 2293

All-Acrylic Emulsion

MARKET SEGMENT: CONSTRUCTION, INDUSTRIAL, ARCHITECTURAL

COMMON APPLICATIONS: TOPCOAT, SEALER

EPS[®] 2293 is a self-crosslinking all-acrylic emulsion offering excellent adhesion and early water resistance for use in clear sealers over tiles and cementitious substrates. Clear and pigmented coatings can be formulated at less than 100 g/l VOC. EPS[®] 2293 offers excellent performance in exterior stain formulations for deck and wood applications and garage floor paint.

FORMULA: EPS[®] 2293 ST1 (261-94) (8/15) Semi-transparent Exterior Wood Stain – 100 g/L VOC

Pounds	Gallons	Raw Material	Supplier	Instructions
568.8	65.0	EPS [®] 2293	EPS	Add raw materials under good agitation
224.9	27.0	Water		
0.8	0.10	Ammonium Hydroxide 28%		
2.0	0.28	Surfynol 104A	Evonik	
8.0	0.96	Foamex 805	Evonik	
10.0	1.09	Tinuvin 5151	BASF	
8.0	1.00	Michem WC 50	Michelman	
22.5	2.85	Texanol	Eastman	
11.0	1.15	Polyphase 663	Arxada	
5.0	0.55	Acrysol RM-8W	Dow	Mix 20 minutes
860.91	99.97	Totals		

Formulation Properties	
Weight Solids	29.03%
Volume Solids	26.46%
Pigment Weight	
Pigment Volume Conc.	0%
VOC Level	98 g/L
Weight/Gallon	8.61 lb/gal

Typical Properties	
Viscosity	70-90 KU
pH	8.5-9.5
Color	Clear Base

Suggested Application Methods: Brush, Roller, Spray

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

7/1/2026

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epsgca.com.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epsgca.com/galleries/pdfs/salesterms.pdf>.